

What is claimed is:

Sub A11
1. An ink level sensing system for determining ink level in an ink reservoir and providing this ink level information to a printing system, the ink level sensing system comprising:

an ink reservoir having a radio frequency interface disposed therein,

a printing device configured for receiving the ink reservoir, the printing device including a radio frequency interface for receiving ink level information that is coupled through the ink reservoir by the radio frequency interface within the ink reservoir.

Sub A12
2. The ink level sensing system of claim 1 further including a sensor electrically connected to the radio frequency interface disposed within the ink reservoir, the sensor providing a sensor output signal indicative of ink level within the ink reservoir to the radio frequency interface.

Sub A13
3. The ink level sensing system of claim 1 wherein the ink reservoir includes a sidewall and wherein the radio frequency interface includes an antenna for coupling a radio frequency signal through the sidewall to the printing system.

4. The ink level sensing system of claim 1 wherein the radio frequency interface within the ink reservoir is enclosed in an encapsulant material and wherein the encapsulant material is at least partially surrounded by ink within the ink reservoir.

5. The ink level sensing system of claim 2 wherein the sensor is a pair of electrodes disposed within the ink reservoir to measure electrical continuity through ink within the ink.

6. The ink level sensing system of claim 2 wherein the sensor is a pair of electrodes disposed within the ink reservoir to measure electrical capacitance between the pair of electrodes.

7. A replaceable printing component for use in a printing system, the replaceable printing component for containing a supply of printing material for use by the printing system to form images on media, the replaceable printing component comprising:

a reservoir for containing printing material; and

a linking device disposed entirely within the reservoir for emitting a signal indicative printing material within the reservoir wherein the reservoir is formed of a material so that the emitted signal passes through the reservoir for providing information to the printing system.

8. The replaceable printing component of claim 7 wherein the linking device is a radio frequency linking device for providing a radio frequency signal.

9. The replaceable printing component of claim 7 wherein the replaceable printing component is a replaceable ink reservoir and wherein the linking device includes a sensor that provides an output signal indicative of ink within the ink reservoir and wherein the output signal is coupled to the printing system by the linking device.

10. The replaceable printing component of claim 7 wherein the replaceable printing component is a replaceable ink reservoir and wherein the linking device includes a sensor having a pair of electrodes disposed within the ink reservoir to measure electrical continuity through ink within the ink reservoir.

11. The ink level sensing system of claim 7 wherein the replaceable printing component is a replaceable ink reservoir and wherein the linking device includes a

Sub A15
sensor having a pair of electrodes that are disposed within the ink reservoir to measure capacitance between the pair of electrodes.

Sub A15
12. The ink level sensing system of claim 7 wherein the reservoir does not contain electrical conductors that extends from within the reservoir to a location outside the reservoir.

Sub A15
13. A printing system having a printer portion and at least one replaceable reservoir, the printer portion and the at least one replaceable reservoir exchanging information therebetween, the printing system comprising:

a first wireless link associated with the replaceable reservoir, the first wireless link disposed entirely within the replaceable reservoir; and

a second wireless link associated with the printer portion, the second wireless link receiving replaceable reservoir information from the first wireless link by transmission of information in a wireless manner.

14. The printing system of claim 13 wherein the first wireless link is a radio frequency transmitter for transmitting a radio frequency signal and the second wireless link is a radio frequency receiver for receiving the radio frequency signal and determining the replaceable reservoir information based thereon.

15. The printing system of claim 13 wherein the replaceable reservoir is a replaceable ink reservoir and wherein the replaceable reservoir information is ink level information for the replaceable ink reservoir.

Sub A15
16. The printing system of claim 13 wherein the first wireless link includes a pair of electrodes are disposed in the replaceable reservoir to measure electrical continuity of ink within the replaceable reservoir.

17. The printing system of claim 13 wherein the first wireless link includes a pair of electrodes disposed in the replaceable reservoir to measure capacitance between the pair of electrodes.

5 18. The printing system of claim 13 where the printer portion is an ink jet printer and wherein the replaceable reservoir contains ink.

19. A method for transferring status information from a replaceable printing component to a printer portion, the method comprising:

10 determining status information of the replaceable printing component using a sensor disposed within the replaceable printing component; and
transferring status information using a wireless link through a sidewall of the replaceable printing component to the printer portion.

15 20. The method of claim 19 wherein the replaceable printing component is an ink reservoir and the printer portion is an ink jet printer and wherein the status information is ink level information in the ink reservoir.

20 21. The method of claim 19 wherein the transferring status information is accomplished by providing a radio frequency signal that couples through a sidewall of the replaceable printing component.

22. A replaceable ink container for providing ink to an inkjet printing system, the replaceable ink container including:

25 a sensing system for sensing parameters of ink within an ink container wherein ink type within the replaceable ink container is determined by the inkjet printing system based on the sensed parameters.

*Sub
A17*

23. ~~The replaceable ink container of claim 22 wherein the sensing system includes a pair of electrodes are disposed in the replaceable ink container for measuring electrical continuity of ink within the replaceable ink container.~~

*Sub
C1
C2
C3
C4
C5
C6
C7
C8
C9
C10
C11
C12
C13
C14
C15
C16
C17
C18
C19
C20
C21
C22
C23
C24
C25
C26
C27
C28
C29
C30
C31
C32
C33
C34
C35
C36
C37
C38
C39
C40
C41
C42
C43
C44
C45
C46
C47
C48
C49
C50
C51
C52
C53
C54
C55
C56
C57
C58
C59
C60
C61
C62
C63
C64
C65
C66
C67
C68
C69
C70
C71
C72
C73
C74
C75
C76
C77
C78
C79
C80
C81
C82
C83
C84
C85
C86
C87
C88
C89
C90
C91
C92
C93
C94
C95
C96
C97
C98
C99
C100*

24. ~~The replaceable ink container of claim 22 wherein the sensing system includes a pair of electrodes for measuring capacitance between the pair of electrodes.~~

25. ~~The replaceable ink container of claim 22 wherein the sensing system senses more than one parameter of ink within the ink container.~~